

Traditional Espresso Machine

Viva S: un incredible tool!

For your comfort, we have extended all the technology to the entire Viva S range, including the Viva S 1 and Viva S 2gr. With its gentle curves, its multiple functions as well as its performance, the Viva S is a reliable and efficient tool, designed to optimize user friendliness and maintenance.



1 group

	Viva S 1
Power	Single phase
Voltage	230 V - 50/60 Hz
Heating Element Power	2100 W
Max. installed Power	10,5 A
Boiler capacity	5,8 L
Heat Exchanger Capacity	1 x 20 cl
Magnetic Pump head	120 L/h
Automatic Boiler Filling	Yes
Security System against lack of water	Yes
Double Gauge	Yes
Steam Arm	1
Prog. Tea Water with adjustable mixed water	Yes
Electronic heating control by temperature Probe and PID System	Yes
"ECO." Function	Yes
CE certified	Yes
Dimensions (W x D x H) mm	430 x 510 x 510
Net weight	42 kg
Gross weight (with packing)	57 kg



Features

- LCD Display accommodate easy monitoring of the machine's operations
- PID* controlled system for automatic correction of the boiler temperature
- ECO function for saving power
- Adjustable Preinfusion on espresso cycles (1 and 2 cups buttons)
- Mixed Tea Water, 2 programmed volumes: no splash, regular flow automatic dosages
- 200 mm Diameter Copper Boiler
- Horizontal heat exchangers of 200 ml each
- Electronic Microprocessor : 5 selections per group
- Automatic boiler filling, built-in rotary pump assembled on silent bloc
- Security system against lack of water to protect the heating element
- Stainless steel arm
- Delivered with:
 - 1 cup filter holder + 2 cups filter holder
 - Operating set (water connection kit)
 - 1 Cleaning set sample

Optional

- 3 cups filter holder
- Possibility to connect to all control systems (cash registers)
- Cappuccino System

Available colors:

