

Viva S: un incredible tool!

For your comfort, we have extended all the technology to the entire Viva S range, including the Viva S 1 and Viva S 2gr. With its gentle curves, its multiple functions as well as its performance, the Viva S is a reliable and efficient tool, designed to optimize user friendliness and maintenance.



2 groups / 710

Features	Viva S 710	
Power	Single phase	3 phases
Voltage	230V-50/60Hz	400V - 50/60Hz
Heating element power	3100W	3800W
Max. installed power	14,5 Amp	6,5 Amp
Boiler	10 L	
Heat exchanger	2 X 20 cl	
Magnetic Pump	120 l/h	
Automatic boiler filling	Yes	
Security system against lack of water	Yes	
Double gauge	Yes	
Steam tap	2	
Manual hot water tap	No	
Prog. hot water	Yes - mixed	
Heating control by pressure switch	No	
Electronic heating control by temperature probe and static relay	Yes	
"ECO." function	Yes	
CE certified	Yes	
Dimensions (W x D x H) mm	710 x 510 x 510	
Net weight	60 Kg	
Gross weight with packing	80Kg	



Features

- LCD Display accommodate easy monitoring of the machine's operations
- PID* controlled system for automatic correction of the boiler temperature
- ECO function for saving power
- Adjustable Preinfusion on espresso cycles (1 and 2 cups buttons)
- Mixed Tea Water, 2 programmed volumes: no splash, regular flow automatic dosages
- 200 mm Diameter Copper Boiler
- Horizontal heat exchangers of 200 ml each
- Electronic Microprocessor : 5 selections per group
- Automatic boiler filling, built-in rotary pump assembled on silent bloc
- Security system against lack of water to protect the heating element
- Stainless steel arm
- Delivered with:
 - 1 cup filter holder per machine
 - 2 cups filter holder per group
 - Operating set (water connection kit)
 - 1 Cleaning set sample

Optional

- 3 cups filter holder
- Possibility to connect to all control systems (cash registers)
- Cappuccino System

Available colors:

